

# Questionnaire


## Rotational movement

<b>Company:</b>	<b>Telephone:</b>
<b>Contact:</b>	<b>Telefax:</b>
<b>Street:</b>	<b>Email:</b>
<b>Postal code, Place:</b>	<b>Date:</b>


### Information

- Number of stations \_\_\_\_\_
- Motion time [t<sub>1</sub>] \_\_\_\_\_ [s]      Rest time [t<sub>2</sub>] \_\_\_\_\_ [s]
- Motion angle [β<sub>1</sub>] \_\_\_\_\_ [°]
- Drive rotates continuously
- Drive stops after every switching operation       Switchings / min \_\_\_\_\_
- Drive reversed      Yes       No
- Emergency stop during the switching operation      Yes       No
- Inching mode during setup      Yes       No
- Desired service life (*normally 8000h*) [L<sub>h</sub>] \_\_\_\_\_ [h]
- Disc on rotary index table
- Outer Ø [D] \_\_\_\_\_ [mm]      Weight [m<sub>s</sub>] \_\_\_\_\_ [kg]
- Workpiece supports
  - Operating radius [r] \_\_\_\_\_ [mm]      Weight [m<sub>A</sub>] \_\_\_\_\_ [kg]      Number \_\_\_\_\_
- Workpieces
  - Operating radius [r] \_\_\_\_\_ [mm]      Weight [m<sub>w</sub>] \_\_\_\_\_ [kg]      Number \_\_\_\_\_


### Mounting position



Mounting position



Mounting position



Mounting position

-> please turn over

# Questionnaire

## Rotational movement

- External forces during motion  
(please send sketch)
- External forces during rest  
(please send sketch)
- Criteria for motor selection:
  - Make: \_\_\_\_\_ Type: \_\_\_\_\_
  - Area of application:  Europe  USA  Others \_\_\_\_\_
  - Voltage: \_\_\_\_\_ [V] Frequency: \_\_\_\_\_ [Hz] Braking voltage: \_\_\_\_\_ [V]
  - Protection class:  IP54  Others \_\_\_\_\_
  - Thermal class:  Standard ISO B  Others \_\_\_\_\_
  - Brake with manual venting: Yes  No

### Remarks

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---