

enquiry form cam gears



Company:	Telephone:
Contact person:	Fax:
Street:	E-Mail:
Postcode, town:	Date:

Type of movement

In principle, the original movement of our curve drives is rotary.

If this original movement is to be converted into a linear movement, please proceed with please continue with **cam gears – linear movements**.

Cam gears – rotational movements

Product group

- GRT rotary indexing table rotoblock index drive
 PAKU-index drive Specific solution

Technical requirements

- Number of stations _____ Stück
 Motion time [t₁] _____ [s] rest time [t₂] _____ [s]
 Motion angle [β₁] _____ [°]
 Drive rotates continuously
 Drive stops after every switching operation switchings /min _____
 Drive reversed yes no
 Emergency stop during the switching operation yes no
 Inching mode during setup yes no
 Desired service life (normally 8000h) [L_n] _____ [h]
 Disc on rotary index table
 Outer Ø _____ [mm] mass [m_s] _____ [kg]
 Workpiece supports
 Operating radius [r] _____ [mm] mass [m_a] _____ [kg] number _____
 Workpieces
 Operating radius [r] _____ [mm] mass [m_w] _____ [kg] number _____



→ please turn to the next page!

Mounting positions:

Mass top

standing

hanging



[1] Cam gear

➤ External forces during motion

(please send sketch)

➤ External forces during rest

(please send sketch)

➤ Criteria for removal:

output rotary table:

output rotary drive:

output centry:

➤ Criteria for engine specification:

• make: _____ type: _____

• areas of application: europe USA others _____

• voltage: _____ [V] frequency: _____ [Hz] braking voltage: _____ [V]

• Protection class: IP54 others _____

• thermal class: standard ISO B others _____

• brake with manual ventilation: yes no

Required quantity

Planned delivery date

General information

Cam gears – straight-line movement

Product group

- GRT rotary indexing table rotoblock index drive
 PAKU-index drive Specific solution

Technical requirements

Stroke of the conveyor [B] for every switching operation _____ [mm]

Motion time [t₁] _____ [s] rest time [t₂] _____ [s]

Motion angle [β₁] _____ [°]

Drive rotates continuously

Drive stops after every switching operation switchings / min _____

Drive reversed yes no

Emergency stop during the switching operation yes no

Inching mode during setup Ja Nein

Desired service life (normally 8000h) [L_h] _____ [h]

Center distance of the conveyor [A] _____ [mm]

Driving wheels:

- number of teeth _____ reference circle-Ø (dd₁) _____ [mm] unit weight _____ [kg]
 number _____

Driven wheels:

- number of teeth _____ reference circle-Ø (dd₁) _____ [mm] unit weight _____ [kg]
 number _____

Workpieces:

- unit weight _____ [kg] number _____

Supports of the workpieces:

- unit weight _____ [kg] number _____

Guide:

- length (l_g) _____ [mm] friction coefficient _____

Transportkette- oder Band

- Graduation _____ [mm] number of chains _____
- Weight of the individual chain _____ [kg]

Configuration

horizontal

vertikal

➤ Please turn to the next page!

